

ISOTEX T

NON-TOXIC FLUID OIL

DESCRIPTION AND APPLICATIONS

- Lubricant for continuous rings.
- Manufacture of Polypropylene bags.
- Needle lubricant for knitwear.
- Lubricant for punching needle.
- Suitable for Polypropylene hydrophobic yarns.

PROPERTIES

- Free from volatile products.
- It doesn't oxidize.
- Does not stain the yarns.
- It does not produce dermatosis when manipulated.

QUALITY LEVEL

Certified NSF 3H-H1 : nº155740

Certified HALAL nº IH-682/2.4/B/76/1/3



TECHNICAL CHARACTERISTICS

	Method	Typical values	Units
Appearance		Clear colorless liquid	-
Viscosity at 40 °C	ASTM D 445	21	cSt
Flash point	ASTM D 92	195	°C
Pour point	ASTM D 97	< -12	°C
Acidity Index	-	< 0,03	mg KOH/gr
Corrosive sulphur free			

HANDLING AND STORAGE

Handling not subject to special requirements. Throughout the lifespan of the product:

- Store separately from other lubricants, chemicals or foodstuffs.
- Protect from sunlight or other heat sources.
- Store at temperatures from 1°C up to +40°C.
- Keep container closed after opening.

The expiry date is 48 months from date of manufacture.

For further information and more product details, packaging and safety data sheets, please refer to our website www.cogelsa.com or contact us at: info@cogelsa.com or export@cogelsa.com

Rev: 11/22

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.