

PREVENT RUST A – 25

CORROSION PREVENTING DEWATERING OIL

DESCRIPTION

- Product based on mineral oil and aliphatic solvents
- With excellent water-displacement properties
- High concentration of corrosion inhibitors.
- Ensures protection against oxidation during long storage time.

APPLICATION

PREVENT RUST A-25 can be applied by brush, roller or spray on the surfaces to be protected.

PREVENT RUST A-25 is recommended for use after processing machined and formed parts. Due to its high water-repellent capacity, this product ensures the total elimination of the presence of water on the surface of machined steel and cast iron parts previously worked with water-miscible refrigerants. After applying the product, it leaves an oily film - of a protective nature - on the metal surface.

PREVENT RUST A-25 is applied by dipping, spraying or by brush or roller to the surfaces to be protected.

TECHNICAL CHARACTERISTICS

	Method	Typical values	Un.
Appearance	-	Clear amber	-
Density at 15 °C	ASTM D 1298	0,815	gr/cm ³
Viscosity at 40 °C	ASTM D 445	6	mm ² /s
Flash point	ASTM D 92	44	°C
Salt spray Cabinet	ASTM B 117	32	hours
Humidity Cabinet	ASTM D 1748	>50	cycles
Film nature	-	oily	-
Film thickness	-	4,0 µ	-

REV: 11/24

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.