

PREVENT RUST GR 10

ANTI-RUST OIL FOR PROFIL AND BAR POLISHING

DESCRIPTION

PREVENT RUST GR 10 is a lubricant based on mineral oil, with a high content of synthetic esters derived from vegetable fatty acids, containing Medium and Extreme Pressure additives

PREVENT RUST GR 10 does not contain chlorinated compounds, heavy metals or any other compound classified by current legislation.

APPLICATIONS

It is used as lubricant for polishing and straightening of profiles and steel bars on benches with hyperbolic rollers or similar.

PREVENT RUST GR 10 is applied pure undiluted

PROPERTIES

- VOC's free.
- Excellent wetting power and dust sedimentation.
- High lubricant and anti-corrosive capacity.
- High Flash Point.
- It doesn't produce fumes or oily mist.
- It doesn't produce lacquers or varnishes.

TECHNICAL CHARACTERISTICS

	Method	Typical values	Un.
Appearance	-	Transparent pale yellow	-
Density at 20 °C	ASTM D 1298	0,85	gr/cm ³
Viscosity at 40 °C	ASTM D 445	10	mm ² /s
Flash point	ASTM D 92	> 170	°C
Copper corrosion (3 h, 50 °C)	ASTM D 130	1a	grado
Wear scar (4 ball test: 40 kg/1 hour/70 °C)	ASTM D 4172	0,40	mm
Humidity cabinet	ASTM D 1748	20	cycles

REV. 12/24

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.