

PREVENT RUST O-157

LUBRICATING AND ANTICORROSIVE FLUID

DESCRIPTION & APPLICATIONS

PREVENT-RUST O-157 is an armament protection fluid for small arms and small and aerial protection fluid for small-calibre armament that ensures its operability at low temperature.

It meets MIL-PRF-14107 D, DEF-STAN 91-102 and **NATO O-157** specifications.

CAUTIONS

Keep containers closed and refer to safety data sheet for handling.

TECHNICAL CHARACTERISTICS

	Method	Typical values	Un.
Appearance	-	Clear liquid	-
Density at 15 °C	ASTM D 1298	0,828	gr/cm ³
Viscosity at 40 °C	ASTM D 445	6 – 8	mm ² /s
Viscosity at -54 °C	ASTM D 445	max. 950	mm ² /s
Flash point	ASTM D 92	160	°C
Pour point	ASTM D 92	max. -52	°C
Acidity Index	ASTM D 974	pass	mg KOH/g
Humidity cabinet	ASTM D 1748	> 400	h

REV: 11/18

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.