

PREVENT RUST O-190

LUBRICATING AND ANTICORROSIVE OIL

DESCRIPTION

PREVENT RUST O-190 is a lubricating oil for anticorrosive protection of automatic weapons.

It meets MIL-PRF-32033 specifications, NATO code O-190. Replaces the old VV L-800 C.

Equivalent standards: DEF STAN 91-79. UK: 6X-13.

ADVANTAGES

PREVENT RUST O-190 has good water separation capacity, optimum protection against corrosion and friction wear.

PREVENT RUST O-190 has effective viscosity-temperature behaviour and reliable ageing stability.

APPLICATION

It can be applied by brush, cloth, spray or immersion.

TECHNICAL CHARACTERISTICS

	Method	Typical values	Un.
Appearance	-	Clear liquid	-
Density at 15 °C	ASTM D 1298	0,89	gr/cm ³
Viscosity at 40 °C	ASTM D 445	11 – 13	mm ² /s
Viscosity at -40 °C	ASTM D 445	max. 7000	mm ² /s
Flash point	ASTM D 92	> 135	°C
Pour point	ASTM D 92	max. -57	°C
Water displacing	FTM 3007	pass	-
Copper corrosion 3h 100 °C	ASTM D 130	1b	grade
Humidity cabinet	ASTM D 1748	> 168	h

REV: 12/18

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.