

PREVENT-RUST S-758

CLEANING, LUBRICATING AND ANTICORROSIVE OIL

DESCRIPTION

PREVENT-RUST S-758 is an oil based on hydrocarbons, anti-corrosion and anti-wear additives, solvent-free, water repellent, with a high flash point and low odour.

Complies with NATO specification code **S-758**, MIL-PRF-63460G Type A and DCSEA 501/A.

APPLICATION

It is used for lubrication, cleaning and protection of automatic weapons.

Applicable with brush and broom.

Working temperature: -50°C to 150°C.

PRECAUTIONS

Keep containers closed. Refer to the safety data sheet.

TECHNICAL CHARACTERISTICS

	Method	Typical values	Un.
Appearance	-	Clear liquid	-
Density at 15 °C	ASTM D 1298	0,86	gr/cm ³
Viscosity at 40 °C	ASTM D 445	14 – 18	mm ² /s
Viscosity at -40 °C	ASTM D 445	max. 5000	mm ² /s
Flash point	ASTM D 92	> 120	°C
Pour point	ASTM D 92	max. -59	°C
Salt spray Cabinet	ASTM B 117	min. 100	hours
Copper corrosion 3h 100 °C	ASTM D 130	1b	grade
Wear scar, 4 ball 1h 40 kg	ASTM D 4172	max. 0,8	mm

REV: 02/24

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.