

PREVENT RUST S-761

LUBRICATING AND ANTICORROSIVE OIL

DESCRIPTION

PREVENT-RUST S-761 is a solvent-free lubricating oil with anticorrosive additives.

It meets NATO specification code S-761, DCSEA 502, and TL 9150-0078.

APPLICATION

Used for lubrication, cleaning and protection of automatic weapons.

Applicable by brush.

Use temperature -40°C to 150°C.

PRECAUTIONS

Keep containers closed. Refer to safety data sheet.

TECHNICAL CHARACTERISTICS

	Method	Typical values	Un.
Appearance	-	Clear liquid	-
Density at 15 °C	ASTM D 1298	0,85	gr/cm ³
Viscosity at 40 °C	ASTM D 445	18 – 20	mm ² /s
Viscosity at -40 °C	ASTM D 445	max. 5000	mm ² /s
Flash point	ASTM D 92	> 160	°C
Pour point	ASTM D 92	max. -57	°C
Salt spray Cabinet	ASTM B 117	min. 72	hours
Copper corrosion 3h 100 °C	ASTM D 130	1b	grade

REV: 12/23

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.