

STANDARD CLEAN FC – 5

SOLVENT BASE CLEANING AGENT

DESCRIPTION AND APPLICATIONS

STANDARD CLEAN FC-5 is a safety degreaser, which can be used to replace cleaning solvents based on gasoline, oil, diesel and others.

STANDARD CLEAN FC-5 is a petroleum hydrocarbon based heavy fraction product which, because of its high flash point (110 °C / W), can be used in cleaning and entrainment applications of fatty contaminants, without the usual risk of these lighter and more flammable solvents, while maintaining high solvent properties. **STANDARD CLEAN FC 5** is VOC-exempt.

STANDARD CLEAN FC-5 can be used in all types of repair shops, truck cleaning, tanks, containers, etc. cleaning of motors and machinery in general. It is also appropriate to clean machined parts. It is harmless on any type of material (aluminum, zinc, magnesium, etc.) or well adhered paint.

PROPERTIES

STANDARD CLEAN FC-5 complies with FDA 172.878 (a) (3) regarding white mineral oils as an additive for food use. NSF C1, Registration No. 149231.

Certified HALAL, nº IH-682/2.4/B/76//1/5
Certified KOSHER



STANDARD CLEAN FC-5 is used pure, undiluted, by dipping, brush, wiper or projection.

TECHNICAL CHARACTERISTICS

	Units	Typical value	Method
Appearance		colorless, transparent	
Density at 15 °C	gr/cm ³	0,81	ASTM D 1298
Flash point	°C	> 100	ASTM D 92
Ignition point	°C	250	
VOC's	%	0	
Biodegradability	%	61	OECD 301
Drying speed (T _{amb} = 20 °C)	hours	> 24	-

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.

STANDARD CLEAN FC – 5

SOLVENT BASE CLEANING AGENT

HANDLING AND STORAGE

Handling not subject to special requirements. Throughout the lifespan of the product:

- Store separately from other lubricants, chemicals or foodstuffs.
- Protect from sunlight or other heat sources.
- Store at temperatures from 1°C up to +40°C.
- Keep container closed after opening.

The expiry date is 48 months from date of manufacture.

For further information and more product details, packaging and safety data sheets, please refer to our website www.cogelsa.com or contact us at: info@cogelsa.com or export@cogelsa.com

Rev: 11/23

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.

COMPANHIA GENERAL DE LUBRICANTES, S.A.
C/ Comercio, 36 P.I. Can Sunyer
08740 Sant Andreu de la Barca, Barcelona, Spain
Telf. +34 93 682 22 20 Fax. +34 93 682 00 55
comercial@cogelsa.com

Export:
Telf. +34 93 635 60 50
export@cogelsa.com
www.cogelsa.com

