

ULTRADEG 40 ATOX

NON-TOXIC CLEANING FLUID

DESCRIPTION

Hydrotreated and additivated oil free of chlorine and heavy metals, as well as any other compound classified in negative lists.

APPLICATION

ULTRADEG 40 ATOX has been specially developed for the cleaning of grooved cylinders. It removes glue, starch and dust residues in the paper/roller contact area.

ULTRADEG 40 ATOX is applied by spraying on rolls at operating temperature, running the rolls at low speed, and with the load reduced to 50%.

PROPERTIES

- Low smoke level.
- High stability.

CERTIFICATIONS

NSF H1 – Register nº 164354

HALAL – Certificate nº IH-682/2.4/B/76/2/41



CHARACTERISTICS

	Unidad	Valores típicos	Método
Appearance	-	Clear liquid	-
Viscosity at 40°C	cSt	34	ASTM D 445
Flash point	°C	208	ASTM D 92
Pour point	°C	-18	ASTM D 97
Density	Kg/l	0,86	ASTM D 1298

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.

ULTRADEG 40 ATOX

NON-TOXIC CLEANING FLUID

HANDLING AND STORAGE

Handling not subject to special requirements. Throughout the lifespan of the product:

- Store separately from other lubricants, chemicals or foodstuffs.
- Protect from sunlight or other heat sources.
- Store at temperatures from 1°C up to +40°C.
- Keep container closed after opening.

The expiry date is 48 months from date of manufacture.

For further information and more product details, packaging and safety data sheets, please refer to our website www.cogelsa.com or contact us at: info@cogelsa.com or export@cogelsa.com