

ULTRALUB EV 3 ATOX

VANISHING OIL FOR METAL STAMPING

DESCRIPTION

ULTRALUB EV 3 ATOX is a transparent, odorless, chlorine-free oil, based on vanishing paraffinic hydrocarbons, with a balanced content of synthetic lubricant additives.

ULTRALUB EV 3 ATOX fully satisfies the requirements of safety and hygiene at work since it does not give off bad smells and does not cause irritation to the skin, throat and eyes.

performance on coated or uncoated steel sheets. It is also recommended for processing aluminium and other non-ferrous alloys.

ULTRALUB EV 3 ATOX is recommended for medium drawing operations on thin sheet metal. There are no compatibility problems with enamelled, varnished, painted, etc. sheet metal. Specially recommended for lid stamping of metal containers and cans with a lighter deformation for the food industry.

APPLICATIONS

ULTRALUB EV 3 ATOX is specially designed for the deformation of metals in processes where it is necessary to avoid subsequent degreasing phases.

ULTRALUB EV 3 ATOX is recommended for the deformation, die-cutting and stamping of any type of metal. It has a particularly good

CERTIFICATIONS

NSF H1, suitable for incidental food contact – nº 149187

Halal Certificate, nº IH-682/2.4/B/76/2/6

Kosher Certificate



TECHNICAL CHARACTERISTICS

	Units	Typical values	Method
Appearance	-	Clear colourless	-
Density at 15 °C	kg/dm ³	0,765	ASTM D 1298
Viscosity at 40 °C	cSt	1,2	ASTM D 445
Flash point	°C	> 60	ASTM D 92
Evaporation Index (eter=1)	-	approx. 110	-

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support.
COGELSA is not liable for damages caused by improper use of the product.

ULTRALUB EV 3 ATOX

VANISHING OIL FOR METAL STAMPING

HANDLING AND STORAGE

Handling not subject to special requirements. Throughout the lifespan of the product:

- Store separately from other lubricants, chemicals or foodstuffs.
- Protect from sunlight or other heat sources.
- Store at temperatures from 1°C up to +40°C.
- Keep container closed after opening.

The expiry date is 48 months from date of manufacture.

For further information and more product details, packaging and safety data sheets, please refer to our website www.cogelsa.com or contact us at: info@cogelsa.com or export@cogelsa.com

Rev: 11/23

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support.
COGELSA is not liable for damages caused by improper use of the product.