

ULTRA MULTI FOOD SPRAY

FOOD GRADE MULTIPURPOSE OIL IN SPRAY

DESCRIPTION

ULTRA MULTI FOOD SPRAY is a multipurpose oil formulated with high purity bases, anticorrosive, antiwear and extreme-pressure additives. It contains PTFE. All its components are approved for incidental food contact (H1 category).

APPLICATIONS

In food and beverage industries, pharmaceutical products and cosmetics:

- As lubricant for: hinges, articulations, small bearings, wires.
- Effective cleaning and lubrication of chains.
- For releasing of oxidised parts such as: screw assemblies, throttlers of bearings, axis assemblies (gears, pulleys, etc.).
- For temporary antioxidant protection and storage of: machine parts, chains, wires, tools, etc.

PROPERTIES

- Good penetrant capacity
- It displaces water
- Excellent wear protection capacity
- It dissolves rust.
- It protects against corrosion.
- It is formulated with components approved by FDA for incidental food contact.

HOW TO USE:

Stir energetically before use. Keep the bottle vertically, as much during the storage as when using it.

QUALITY LEVEL

Approved NSF H1, nº Register 149233
Certified HALAL, nº IH-682/2.4/B/76/3/13



TECHNICAL CHARACTERISTICS

(concentrate)	Method	Typical values	Un.
Appearance	-	colourless liquide	-
Density at 15°C.	ASTM D-1298	0,85	gr/cm ³
Viscosity at 40°C.	ASTM D-445	15,8	cSt
Flash point	ASTM D-92	195	°C
Pour point	ASTM D-97	-12	°C
Welding load	ASTM D 2783	250	kg
Wear scar, 4 balls test	ASTM D 4172	0,29	mm

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.

ULTRA MULTI FOOD SPRAY

FOOD GRADE MULTIPURPOSE OIL IN SPRAY

HANDLING AND STORAGE

Handling not subject to special requirements. Throughout the lifespan of the product:

- Store separately from other lubricants, chemicals or foodstuffs.
- Protect from sunlight or other heat sources.
- Store at temperatures from 1°C up to +40°C.
- Keep container closed after opening.

The expiry date is 60 months from date of manufacture.

For further information and more product details, packaging and safety data sheets, please refer to our website www.cogelsa.com or contact us at: info@cogelsa.com or export@cogelsa.com

REV: 11/22

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.

COMPANHIA GENERAL DE LUBRICANTES, S.A.
C/ Comercio, 36 P.I. Can Sunyer
08740 Sant Andreu de la Barca, Barcelona, Spain
Telf. +34 93 682 22 20 Fax. +34 93 682 00 55
comercial@cogelsa.com

Export:
Telf. +34 93 635 60 50
export@cogelsa.com
www.cogelsa.com

