

WHITE OIL FILANTE

MEDICINAL WHITE PETROLEUM JELLY

DESCRIPTION

Food and medicinal grade tacky petroleum jelly with appearance of slightly translucent, creamy paste free of odour.

PROPERTIES

- ⇒ High stability due to its high purity.
- ⇒ Tacky effect and adhesive properties.
- ⇒ Odourless

APPLICATIONS

WHITE OIL FILANTE is indicated mainly for medicinal cosmetic uses as base component for creams (also as softener, excipient, stabilizer) and as lubricant for machinery in food industry.

It also extends its application to many kinds of industries as textile, veterinary, agricultural, adhesives, plastics, packaging, etc.

QUALITY LEVEL:

DAB 2019 (DAB 10)
European Pharmacopoeia, 9th edition
FDA {21 CFR 172.878 y 178.3620 (a)}
US Pharmacopoeia, USP 42-NF37
British Pharmacopoeia, 2019 edition
Pharmacopoeia Francaise, 11 th edition
CODEX 1998
Meets DEF STAN 91-38 - Petrolatum,
technical, NATO Code S-743.
Certificate HALAL / KOSHER



TECHNICAL CHARACTERISTICS

	Units	Typical values	Norm
Appearance	-	White translucent	-
Density at 15 °C	gr/cm ³	0,858	ASTM D 1298
Viscosity at 100 °C	cSt	6,5	ASTM D 445
Flash point	°C	200	ASTM D 92
Dropping point	°C	57,4	ASTM D 127/60
Aniline point	°C	120	ASTM D 611
Unworked Penetration at 25 °C	mm x 10 ⁻¹	164	ASTM D 217
Worked Penetration 60 strokes at 25°C	mm x 10 ⁻¹	234	ASTM D 217

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.

WHITE OIL FILANTE

MEDICINAL WHITE PETROLEUM JELLY

HANDLING AND STORAGE

Handling not subject to special requirements. Throughout the lifespan of the product:

- Store separately from other lubricants, chemicals or foodstuffs.
- Protect from sunlight or other heat sources.
- Store at temperatures from 1°C up to +40°C.
- Keep container closed after opening.

The expiry date is 48 months from date of manufacture.

For further information and more product details, packaging and safety data sheets, please refer to our website www.cogelsa.com or contact us at: info@cogelsa.com or export@cogelsa.com

Rev: 07/24

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.

COMPañIA GENERAL DE LUBRICANTES, S.A.
C/ Comercio, 36 P.I. Can Sunyer
08740 Sant Andreu de la Barca, Barcelona, Spain
Telf. +34 93 682 22 20 Fax. +34 93 682 00 55
comercial@cogelsa.com

Export:
Telf. +34 93 635 60 50
export@cogelsa.com
www.cogelsa.com

