

ULTRADEG 38 NF

NON-FLAMMABLE DIELECTRIC SOLVENT

DESCRIPTION

ULTRADEG 38 NF is a new technology solvent, colourless, odourless, non-flammable, especially suitable to cleaning electrical systems where a non-conductive fluid is required.

It can be used for cleaning oils, greases, waxes, charcoal, environmental dust... etc, of any metal or plastic part.

It is a non-toxic product that does not cause irritation problems.

ULTRADEG 38 NF is a product very compatible with metals: aluminium, copper, steels, bronze, magnesium alloys and zinc. It is also compatible with plastics and elastomers: EPDM, nitrile, natural rubber, acrylic, polypropylene, polycarbonate, polyester, epoxy, ... etc.

ULTRADEG 38 NF leaves no residue and evaporates completely.

PROPERTIES

- Non-flammable.
- Non-toxic.
- Excellent dielectric properties.
- Compatible with metals, plastics and elastomers.

METHOD OF USE

Can be used with brush, rags, spray and immersion.

CHARACTERISTICS

	Units	Typical values	Method
Appearance	-	clear liquid	-
Density at 15 °C	kg/dm ³	1,6	ASTM D 1298
Viscosity at 20 °C	cSt	< 5	ASTM D 445
Pour point	°C	< -30	ASTM D 97
Boiling point	°C	> 50	ASTM D 86
Dielectric Breakdown Voltage	kV	40	ASTM D 877

Rev: 05/20

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.