

ULTRADEG SD ATOX

SUGAR DISSOLVING LUBRICANT

DESCRIPTION

ULTRADEG SD ATOX is a water-soluble fluid based on biodegradable components.

APPLICATIONS

ULTRADEG SD ATOX is used in the sugar processing industries for the removal of sugar deposits and caramel crust and the lubrication of machine components.

ULTRADEG SD ATOX is ready to use fluid and applied by brush allowing to react or by spray applying a thin spray film to prevent contamination. Please observe the instructions of the equipment manufacturer.

PROPERTIES

- ✓ Is practically odorless which guarantees a more pleasant working environment.
- ✓ Prevents re-adhesion of sugar and new accumulations of sugar.
- ✓ Reduces the time of maintenance and the number of expensive shutdowns of the equipment, increasing the performance and reliability.
- ✓ Anticorrosive capacity.

CERTIFICATIONS

- **H1 (incidental contact – GJ 1428007) and A1 (general cleaners GJ 1428007)**
- **HALAL**



TECHNICAL CHARACTERISTICS

	Units	Typical values	Method
Appearance	-	Clear liquid	-
Density at 15 °C	kg/dm ³	1,0	ASTM D 1298
PH value	-	8,2	-

Rev: 10/25

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support.
COGELSA is not liable for damages caused by improper use of the product.