

ROS OIL A 22 FE

EMULSIFIABLE OIL FOR TEXTILE MACHINERY

DESCRIPTION

Special white oil with additives that improve lubricity, oxidation stability, emulsifiers and corrosion protection. Formulated with emulsifying agents that facilitate the removal of the fabric due to its easy incorporation into washing baths.

APPLICATIONS

Particularly suitable for the lubrication of spinning rings and travellers on circular and linear knitting machines.

PROPERTIES

- Emulsifiable oil, which allows easy removal of the yarn with a simple wash.
- Resistant to aging and stable to oxidation.
- Great moisturizing power and excellent capillarity.
- Does not form resins or polymerize.

TECHNICAL CHARACTERISTICS

	Method	Typical values	Un.
Appearance	Transparent		
Density at 15 °C	ASTD D 1298	0,865	gr/cm ³
Viscosity at 40 °C	ASTM D 445	22	cSt
Viscosity Index	ASTM D 2270	110	-
Flash point	ASTM D 92	200	°C
Pour point	ASTM D 97	-27	°C

Rev: 12/18

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.