

ROS OIL A 22 IN

KNITTING MACHINE OIL

DESCRIPTION

Special highly refined oil with additives to improve lubricity, oxidation stability and corrosion protection. It is formulated with emulsifying agents to allow an easy wash out from fabric with alkaline agents.

APPLICATIONS

Especially suitable for lubrication of needles and plates in circular knitting machines.

PROPERTIES

- High lubricant capacity that ensures a long life of needles and plates.
- Decreases the operating temperature of the machine due to its low friction operation.
- Excellent surfactant power to give more efficiency to the lubrication along the needle.
- Easily washable thus decreasing production losses due to lubricant staining.

TECHNICAL CHARACTERISTICS

	Method	Typical values	Un.
Appearance		Pale yellow transparent	
Density at 15 °C	ASTD D 1298	0,850	gr/cm ³
Viscosity at 40 °C	ASTM D 445	22	cSt
Viscosity Index	ASTM D 2270	119	-
Flash point	ASTM D 92	200	°C
Pour point	ASTM D 97	-27	°C

Rev: 01/25

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.