TECHNICAL INFORMATION

ULTRABEN SYNT 10004 TF

HIGH PERFORMANCE VALVE SEALING AND LUBRICATING GREASE

DESCRIPTION

Valve sealing and lubricating grease made with a blend of synthetic oils, inorganic thickener and additives for improving performance, including special micronized solid lubricants.

APPLICATIONS

ULTRABEN SYNT 10004 TF is designed for valve sealing and lubrication operating with petroleum products, cold and hot air. Not suitable for hot water, strong alkalis and aromatic solvents.

PROPERTIES

- Excellent emergency lubrication properties due to high content in special micronized lubricants.
- High sealing effect thanks to high consistency and special high viscosity base oils.
- Optimum performance even in presence of petroleum products and most hydrocarbon solvents.
- Excellent corrosion protection.

TECHNICAL CHARACTERISTICS

	Method	Typical values	Un.
Appearance	Visual	Black grease	-
Consistency NLGI	ISO 2137	4	-
Penetration at 25 ºC	ASTM D-217	185	mm^{-1}
Dropping point	ASTM D 566	None	ºC
Welding load, 4 ball test	ASTM D 2596	400	kg
Base oil viscosity at 40ºC	ASTM D 445	10.000	cSt

Rev: 10/22

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.

COMPAÑIA GENERAL DE LUBRICANTES, S.A.
C/ Comercio, 36 P.I. Can Sunyer
08740 Sant Andreu de la Barca, Barcelona, Spain
Telf. +34 93 682 22 20 Fax. +34 93 682 00 55
comercial@cogelsa.com

Export:
Telf. +34 93 635 60 50
export@cogelsa.com

www.cogelsa.com

ISO 9001
ISO 14001
BUREAU VERITAS
Certification